

## TECHNICAL DATASHEET CERAMIC TERMINAL BLOCKS 10A-20A



These terminals allow the connection star-delta three-phase motors or two separate motors. Thanks to the excellent thermal resistance properties conferred by ceramics, they find application in machinery such as electric ovens, motors with high operating temperatures, equipment where very high temperature resistance is required, such as smoke and heat extraction fans. These terminal blocks are also used for star-delta switching of three-phase heaters.

### TECHNICAL DETAILS

<b>Housing material:</b>	Technical Ceramic C110
<b>Inserts material:</b>	Brass
<b>Screws material:</b>	Galvanised steel
<b>Temperature of use:</b>	-5 °C ÷ 350 °C
<b>Housing temperature :</b>	Until 1000°C
<b>Inserts temperature:</b>	Until 350 °C
<b>Thermal shock resistance:</b>	Good
<b>Chemical resistance:</b>	Excellent
<b>Electric strength of ceramic:</b>	Minimum 10 kV/mm
<b>Color:</b>	White

### CERTIFICATION and CONFORMITY

<b>Comply with:</b>	CEI EN 60998-1:2004 , EN 60998-2-1:2004
<b>Comply with:</b>	2011/65/EU (restriction of the use of certain hazardous substances - RoHS)

### APPLICATIONS

- ▶ electrical wiring industrial and domestic

### FEATURE

- ▶ high temperature resistance
- ▶ non inflammable

LAST REVISION 05-09-2018

The informations contained in this data sheet replace all preceding data sheets and are based on the current knowledge at the date of publication. Are given in good faith, without warranty, express or implied, the user must verify the suitability and completeness of such information according to the specific use. The original language of this data sheet is italian, the translation is made in good faith and to the best knowledge. The photos the logos and the marks TecnicalCeramic and TecnicalCeramic.store are exclusive property of SAVAR Srl. Reproduction and spread, also partial, of them are forbidden without written authorization from SAVAR Srl